





Bright, Natural Light. Quick Installation.

Fill Every Room with Natural Light

Daylight is powerful, which is why every room deserves to be filled with it. The VELUX Sun Tunnel® Skylight's versatile design offers quick and easy installation, letting you enjoy a new world of natural light in as soon as an afternoon.

Meet Your Sun Tunnel® Skylight

- Clear UV Resistant Dome
 Captures the most light possible with a clear dome.
- Adjustable Pitch Adapter Pivots the tunnel towards the sun and allows for easier installation.
- One-Piece Metal Flashing
 Provides maximum light capturing while
 guaranteeing no water penetration.
- Adjustable Elbow (Rigid Tunnel)
 Rotates 45°. Elbows are 12" long.
- **Tunnel Assembly System**Offers quick and easy installation of tunnel.

Rigid Tunnel Option - 99% reflective, 24" sections assemble quickly with the **Flexi Loc™** tunnel system.

Flexible Tunnel Option - Faster method of installation with seamless all-in-one elbow and tunnel system.

6 Solar Night Light (Rigid Tunnel)
The Solar Night Light provides soft, soothing light when natural light isn't available.*
Optional add-on.

Federal Solar
Tax Credit

on product and installation¹

*Must be purchased with sun tunnel to receive federal tax credit. **Federal tax credit based off total product and installation cost. Visit veluxusa.com/go-solar

Pre-Assembled Ceiling Ring Diffuses light into the space using an energy-efficient, frosted dual-diffuser system. Diffuser options can be customized to meet décor and style.



Choosing Your Sun Tunnel® Skylight

There are several sun tunnel options for you to choose from, but picking one for your home doesn't have to be complicated. We'll make it easy!

Two Types of Tunnels

Rigid Tunnels

- · Designed as a highly reflective tunnel, the rigid tunnel lets in the most light
- Enables longer runs
- Excellent for areas with less sunlight
- Easy assembly of tunnel with Flexi Loc™ system

Flexible Tunnels

- · The flexible sun tunnel is movable and able to bend around tight. obstructed spaces
- · Fast and easy installation
- · Softens and provides additional light diffusion
- Excellent for sunny areas and short runs









10". 14". & 22" Model TGR

Low-Profile Metal Flashing:

- Best for south, west, and east-facing roofs
- · Parallel to roof and designed to blend with roofline



Model TMF



10" & 14" Model TMR

Pitched Metal Flashing:

- · Provides consistent light distribution throughout the day
- · Provides straighter tunnel run through many different roof pitches



Low-Profile Flat Glass **Flashing:** (Available in 14" only)

- · Low-profile glass design creates sleek appearance
- · Perfect for developments where local ordinances do not allow acrylic domes on the roof



Model TCR

Curb Metal Flashing:

(Available in 14" only)

- · One-piece metal curb-mounted flashing
- · Ideal for low roof slopes and/or tile roofing applications









Model TZR

Model TZRL

Wildfire Glass Pan Flashing (TZRO): (Available in 14" only)

Wildfire Glass Curb Mount (TZR/TZRL): (Available in 14" only)

- · Features a fireproof tempered diamond wire flat glass, allowing it to pass an ASTM E108 Class A Burn Brand Test
- · Available for tile and shingle roof installations
- The TZRL model includes step-flashing for a quick and easy installation on shingle roofing
- Also available in Laminated Impact Resistant Glass in high velocity hurricane zones (except areas requiring Miami-Dade Notice of Acceptance)







Decorative Diffuser Options: (Available in 10" & 14" only)

 Select from a range of micro-engineered decorative diffusers to increase interior aesthetics and visual appeal.

Ruhhlas

3 VELUX Sun Tunnel® Skylights veluxusa.com

Accessories

Sun Tunnel® Skylight Accessories

NEW

The VELUX Sun Tunnel Solar Night Light



Produces constant, low-level light after the sun sets so you can enjoy light day and night. *Available for all residential rigid sun tunnels*.

*Tax credit based off total installation cost. Visit veluxusa.com/ao-solar

Daylight Controller (ZTP) **Power Supply** (ZZZ 233)



Allows the user to control the amount of daylight that enters a room. Perfect for rooms that require room darkening. Available in 14" & 22" rigid tunnels.

Rigid Tube (ZTR)



Additional 24" tube section when tunnel length exceeds 48". *Available in bulk quantities.*

Suspension Wire kit (ZTZ 203)



12-gauge wire and fastener set to secure longer tunnel sections.

Universal Electric Light Kit (ZTL)



c(UL)us

Energy efficient electric light with a GU24 base designed for residential sun tunnels. Easy installation and compatible with energy efficient CFL and LED bulbs. GU24 bulb sold separately.

Vapor Barrier (ZTY)



Molded, impermeable, thin vapor barrier sheet prevents moisture from penetrating ceiling opening. Recommended for new installations in cold climates.

Elbows (ZTE)



Durable, interchangeable 45° elbows that are 12" long and come in 3 diameters. Multiple elbows can be joined together with rotating couplers.

Rotating Coupler (ZTZ 211)



Easy to install tunnel and elbow coupler that enables quick tunnel connections. Rotating joint helps align tunnel sections.

Energy Kit (ZTC)



Designed to increase the energy efficiency of the VELUX Sun Tunnel® Skylight while enabling it to be ENERGY STAR® certified.

Diffusion Enhancer (ZTZ 209)



A highly reflective, obscure 6" band designed to diffuse direct sunlight.

Pitched Tile Flashing (ZTM)



Painted, malleable, aluminum sheet provides a water-tight flashing without the use of sealants. Available for 10" and 14".

Curb-mounted Tile Flashing (ECW)



Pliable, pleated, curb-mounted tile flashing system engineered for tile roofing material.

Available for 14".

5 VELUX Sun Tunnel® Skylights veluxusa.com

Product Details

Rigid Units Include:

- Flashing complete with dome
- Two 12" elbows
- 24" extension
- Ceiling diffuser assembly complete with frosted diffuser

Flexible Units Include:

- · Flashing complete with dome
- 8' of tunnel for 14" units
- 12' of tunnel for 22" units
- Ceiling diffuser assembly complete with frosted diffuser

Note: Additional tunnel available as needed

Square Footage Recommendations:

- 10" Rigid (TGR/TMR) up to 200 sq.ft.
- 14" Rigid (TGR/TMR/TLR/TCR) up to 325 sq.ft.
- 22" Rigid (TGR) up to 625 sq.ft.
- 14" Flex (TGF/TMF) up to 150 sq.ft.
- 22" Flex (TGF) up to 325 sq.ft.

Note: These are all general guidelines. Sun angles, length of tunnel, roof orientation, tunnel straightness, and room consideration may affect this number.

Maximum Tunnel Length Recommendations:

- \bullet Rigid 10" is 20' and 14" is 30' (TGR/TMR/TLR/TCR)
- Rigid 22" is 40' (TGR)
- Flex 14" (TGF/TMF) is 8'
- Flex 22" (TGF) is 12'

Note: Orientation of roof and straightness of tunnel are both important factors.

Other Options:

- Impact models (for hurricane prone areas)
- Commercial Sun Tunnel® Skylights for school and industrial applications

<u>Authorized VELUX Dealer</u>

Ultra Beauty, Inc. **(386)756-1200**

UBSkylights.com